
# PXF6052C Datasheet



## Product Name // No Cable, Rear panel mount fiber connector for OS1 cable





### // Product Description:

- O Rear Panel Mount Fiber Connector
- 0 Sealed to IP66, IP68, IP69K when mated with compatible connector
- 0 no cable options, or pre-terminated 1M available
- 0 Duplex LC type fiber connector

- O Choices of OS1, OM1 and OM3 cables for single or multimode
- PXP6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with flex fiber connector PXF6050

#### // General Information:

**Product Display Title:** 

**Product Family:** 

**Product Series:** 

**Body Material:** 

Contact Type:

Coupling Type:

Diameter Over Coupling Ring Mm:

Fibre Mode:

Flamability Rating:

Function:

Ip Rating:

Max Operating Temperature: Min Operating Temperature:

Rear Panel Mount Fiber Connector

Circular Fiber Connectors

6000 Series - Duplex LC Fiber Buccaneer

Polyamide (PA)

LC Fiber

30 Degree coupling

32mm

OS1

UL94V-0

Rear Panel Mount to Double LC Connector Double Ended Fiber Cable

IP66, IP68, IP69K

+70°C

-25°C

#### // Product PDF Links



6000 Series Fiber connectors...

#### // Product 3D CAD Model Links



PXF6052C3D CAD Model