## PXM6010/02P/CR/0709/SN Datasheet bulgin



Product Name // Flex Cable Connector PXM6010 Series 2 **Contact Plug Crimp/Solder Termination (contacts available** separately) 7mm-9mm Cable (Yellow Gland) Metal Body **With Braid Termination** 





## // Product Description:

- 0 Flex Cable Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Plug
- O 2 Contacts
- 0 Crimp/solder termination with contacts and fitting tool available separately
- 0 Metal Body With Braid Termination
- 0 Cable acceptance 7mm-9mm diameter
- Gland Pack PXP6088 available separately to accomodate all sizes
- PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXM6011 Series Inline and PXM6012 Series Front Panel Mount Connectors

## // General Information:

**Product Display Title: Product Family:** 

**Product Series:** 

Approvals:

**Body Colour:** 

**Body Material: Body Material Type:** 

Contact Type:

Coupling Type:

**Current Max:** 

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature:

**Number Of Contacts:** 

Rohs Compliant:

Salt Spray Corrosion Test:

Voltage Max:

Flex Cable Connectors

Circular Power Connectors

6000 Series Buccaneer

UL

Metallic Grey

**Brass** 

Metal Body With Braid Termination

Plug Contact Push-Twist

16A, 11A

32mm Flex Cable Connector

>106MΩ @500V DC

IP66, IP68, IP69K

9mm

14AWG

18AWG 2.5mm2

0.75mm2 +120°C

-40°C 2 Contacts

EN60068-2-11 Test Ka Salt Mist



