## PXM6010/02S/CR/0405/SN Datasheet bulgin



Product Name // Flex Cable Connector PXM6010 Series 2 **Contact Socket Crimp/Solder Termination (contacts** available separately) 4mm-5mm Cable (Dark Grey Gland) **Metal Body With Braid Termination** 





## // Product Description:

- 0 Flex Cable Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Socket
- 0 2 Contacts
- 0 Crimp/solder termination with contacts and fitting tool available separately
- 0 Metal Body With Braid Termination
- 0 Cable acceptance 4mm-5mm diameter
- Gland Pack PXP6088 available separately to accomodate all
- PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXM6011 Series Inline and PXM6012 Series Front Panel Mount Connectors

## // General Information:

**Product Display Title: Product Family:** 

**Product Series:** 

Approvals:

**Body Colour:** 

**Body Material: Body Material Type:** 

Contact Type:

Coupling Type: **Current Max:** 

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2:

Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** 

Rohs Compliant: Salt Spray Corrosion Test:

Voltage Max:

Flex Cable Connectors

Circular Power Connectors

6000 Series Buccaneer

UL

Metallic Grey

Brass

Metal Body With Braid Termination

Socket Contact Push-Twist 16A, 11A

32mm

Flex Cable Connector >106MΩ @500V DC

IP66, IP68, IP69K

5mm

14AWG 18AWG 2.5mm2 0.75mm2

+120°C -40°C 2 Contacts

EN60068-2-11 Test Ka Salt Mist



