PXM6010/04S/CR/0709 Datasheet



Product Name // Flex Cable Connector PXM6010 Series 4 Contact Socket Crimp/Solder Termination (contacts available separately) 7mm-9mm Cable (Yellow Gland) Metal Body No Braid Termination





mage not found or type unknown

// Product Description:

- Flex Cable Connectors
- Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- O 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Socket
- 4 Contacts
- Crimp/solder termination with contacts and fitting tool available separately
- Metal Body No Braid Termination
- O Cable acceptance 7mm-9mm diameter
- Gland Pack PXP6088 available separately to accommodate all sizes
- PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with PXM6011 Series Inline and PXM6012 Series Front Panel Mount Connectors

// General Information:

Product Display Title:

Product Family:

Product Series:

Body Colour:

Body Material: Body Material Type:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:
Max Contact Accomodation Awg:

Min Contact Accomodation Awg:
Max Contact Accomodation Mm2:

Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature:

Min Operating Temperature: Number Of Contacts:

Salt Spray Corrosion Test:

Voltage Max:

Rohs Compliant:

Flex Cable Connectors

Circular Power Connectors

6000 Series Buccaneer Metallic Grey

Brass

Metal Body No Braid Termination

Socket Contact Push-Twist

10A, 4A, 7A

32mm

Flex Cable Connector $>10^6 M\Omega$ @500V DC

IP66, IP68, IP69K

9mm

7mm

18AWG

20AWG

0.75mm2

0.5mm2

+120°C -40°C

4 Contacts

EN60068-2-11 Test Ka Salt Mist

277V

// Product PDF Links

6000 Series power connectors...

6000 Series metal body power...

// Product 3D CAD Model Links

PXM6010/04S/CR/07093D CAD Model