
PXM6011/02P/CR/0507/SN Datasheet bulgin



Product Name // Inline Cable Connector PXM6011 Series 2 **Contact Plug Crimp/Solder Termination (contacts available** separately) 5mm-7mm Cable (White Gland) Metal Body With **Braid Termination**







// Product Description:

- Inline Cable Connectors 0
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Plug
- O 2 Contacts
- 0 Crimp/solder termination with contacts and fitting tool available separately
- 0 Metal Body With Braid Termination
- 0 Cable acceptance 5mm-7mm diameter
- Gland Pack PXP6088 available separately to accomodate all
- PXM6082 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXM6010 Series Flex Connectors

// General Information:

Product Display Title:

Product Family: Product Series:

Approvals:

Body Colour:

Body Material:

Body Material Type:

Contact Type:

Coupling Type: **Current Max:**

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2:

Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:**

Rohs Compliant:

Salt Spray Corrosion Test: Voltage Max:

Inline Cable Connectors Circular Power Connectors 6000 Series Buccaneer

UL

Metallic Grey

Brass

Metal Body With Braid Termination

Plug Contact Push-Twist 16A, 11A

32mm

Inline Cable Connector >106MΩ @500V DC

IP66, IP68, IP69K

7mm 14AWG 18AWG 2.5mm2 0.75mm2 +120°C -40°C

2 Contacts

EN60068-2-11 Test Ka Salt Mist

// Product PDF Links





// Product 3D CAD Model Links

