# PXM6011/04P/CR/0709/SN Datasheet bulgin



## Product Name // Inline Cable Connector PXM6011 Series 4 **Contact Plug Crimp/Solder Termination (contacts available** separately) 7mm-9mm Cable (Yellow Gland) Metal Body **With Braid Termination**





hage not found or type unknown

#### // Product Description:

- 0 Inline Cable Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Socket
- 0 4 Contacts
- 0 Crimp/solder termination with contacts and fitting tool available separately
- 0 Metal Body With Braid Termination
- 0 Cable acceptance 7mm-9mm diameter
- 0 Gland Pack PXP6088 available separately to accomodate all sizes
- 0 PXM6082 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXM6010 Series Flex Connectors

#### // General Information:

**Product Display Title:** 

**Product Family:** 

**Product Series: Body Colour:** 

**Body Material: Body Material Type:** 

Contact Type:

Coupling Type:

**Current Max:** 

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** 

**Rohs Compliant:** 

Salt Spray Corrosion Test:

Voltage Max:

Inline Cable Connectors

Circular Power Connectors

6000 Series Buccaneer Metallic Grey

**Brass** 

Metal Body With Braid Termination

Socket Contact

Push-Twist 10A, 4A, 7A

32mm

Inline Cable Connector

>106MΩ @500V DC

IP66, IP68, IP69K

9<sub>mm</sub> 7mm

18AWG

20AWG

0.75mm2

0.5mm2

+120°C -40°C

4 Contacts

EN60068-2-11 Test Ka Salt Mist

277V

### // Product PDF Links

6000 Series power connectors.

#### // Product 3D CAD Model Links

PXM6011/04P/CR/0709/SN3D CAD Model