












PXM6011/16P/CR/0405 Datasheet

Product Name // Inline Cable Connector PXM6011 Series
16 Contact Plug Crimp/Solder Termination (contacts available separately) 4mm-5mm Cable (Dark Grey Gland)
Metal Body No Braid Termination

 [View Product Page](#)



// Product Description:

-  Inline Cable Connectors
-  Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
-  30 degree push twist locking, tamperproof lock prevents accidental un-mating
-  Plug
-  16 Contacts
-  Crimp/solder termination with contacts and fitting tool available separately
-  Metal Body No Braid Termination
-  Cable acceptance 4mm-5mm diameter
-  Gland Pack PXP6088 available separately to accommodate all sizes
-  PXM6082 Sealing Cap available separately to maintain IP rating of unmated connectors
-  Mate with PXM6010 Series Flex Connectors

// General Information:

| | |
|---------------------------------|---------------------------------|
| Product Display Title: | Inline Cable Connectors |
| Product Family: | Circular Power Connectors |
| Product Series: | 6000 Series Buccaneer |
| Approvals: | UL |
| Body Colour: | Metallic Grey |
| Body Material: | Brass |
| Body Material Type: | Metal Body No Braid Termination |
| Contact Type: | Plug Contact |
| Coupling Type: | Push-Twist |
| Current Max: | 1.5A, 2A, 3A |
| Diameter Over Coupling Ring Mm: | 32mm |
| Function: | Inline Cable Connector |
| Insulation Resistance: | >10 ⁶ MΩ @500V DC |
| Ip Rating: | IP66, IP68, IP69K |
| Max Cable Entry Size: | 5mm |
| Min Cable Entry Size: | 4mm |
| Max Contact Accomodation Awg: | 22AWG |
| Min Contact Accomodation Awg: | 26AWG |
| Max Contact Accomodation Mm2: | 0.34mm ² |
| Min Contact Accomodation Mm2: | 0.14mm ² |
| Max Operating Temperature: | +120°C |
| Min Operating Temperature: | -40°C |
| Number Of Contacts: | 16 Contacts |
| Rohs Compliant: | Yes |
| Salt Spray Corrosion Test: | EN60068-2-11 Test Ka Salt Mist |
| Voltage Max: | 60V |

// Product PDF Links

 [6000 Series power connectors...](#)

 [6000 Series metal body power...](#)

// Product 3D CAD Model Links

 [PXM6011/16P/CR/04053D CAD Model](#)