PXM6011/04P/CR/0910/SN Datasheet



Product Name // Inline Cable Connector PXM6011 Series 4
Contact Plug Crimp/Solder Termination (contacts available separately) 9mm-10mm Cable (Light Grey Gland) Metal
Body With Braid Termination





mage not found or type unknown

// Product Description:

- O Inline Cable Connectors
- Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Socket
- 4 Contacts
- Crimp/solder termination with contacts and fitting tool available separately
- Metal Body With Braid Termination
- O Cable acceptance 9mm-10mm diameter
- Q Gland Pack PXP6088 available separately to accommodate all sizes
- PXM6082 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with PXM6010 Series Flex Connectors

// General Information:

Product Display Title:

Product Family:

Product Series: Body Colour:

Body Material:

Body Material Type:

Contact Type:

Coupling Type: Current Max:

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg:

Max Contact Accomodation Mm2:
Min Contact Accomodation Mm2:
May Operating Temperature

Max Operating Temperature: Min Operating Temperature:

Number Of Contacts: Rohs Compliant:

Salt Spray Corrosion Test:

Voltage Max:

Inline Cable Connectors

Circular Power Connectors

6000 Series Buccaneer

Metallic Grey

Brass

Metal Body With Braid Termination

Socket Contact

Push-Twist 10A, 4A, 7A

32mm

Inline Cable Connector

>10⁶MΩ @500V DC

IP66, IP68, IP69K

10mm 9mm

20AWG

16AWG

1.5mm2

0.5mm2

+120°C

-40°C 4 Contacts

Yes

EN60068-2-11 Test Ka Salt Mist

277V

// Product PDF Links

6000 Series power connectors...

6000 Series metal body power...

// Product 3D CAD Model Links

PXM6011/04P/CR/0910/SN3D CAD Model