Circular Power Connectors / 6000 Series Buccaneer

PXM6011/04S/CR/0405/SN Datasheet



View Product Page

Product Name // Inline Cable Connector PXM6011 Series 4 Contact Socket Crimp/Solder Termination (contacts available separately) 4mm-5mm Cable (Dark Grey Gland) Metal Body With Braid Termination



// Product Description:

- O Inline Cable Connectors
- O Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Socket
- O 4 Contacts
- O Crimp/solder termination with contacts and fitting tool available separately

hage not found or type unknown

- O Metal Body With Braid Termination
- O Cable acceptance 4mm-5mm diameter
- O Gland Pack PXP6088 available separately to accomodate all sizes
- O PXM6082 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PXM6010 Series Flex Connectors

// General Information:

Product Display Title: Product Family: **Product Series:** Body Colour: Body Material: Body Material Type: Contact Type: Coupling Type: Current Max: Diameter Over Coupling Ring Mm: Function: Insulation Resistance: Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: **Rohs Compliant:** Salt Spray Corrosion Test: Voltage Max:

Inline Cable Connectors **Circular Power Connectors** 6000 Series Buccaneer Metallic Grey Brass Metal Body With Braid Termination Socket Contact Push-Twist 10A, 4A, 7A 32mm Inline Cable Connector >10⁶MΩ @500V DC IP66, IP68, IP69K 5mm 4mm 20AWG 16AWG 1.5mm2 0.5mm2 +120°C -40°C 4 Contacts Yes EN60068-2-11 Test Ka Salt Mist 277V



// Product 3D CAD Model Links

PXM6011/04S/CR/0405/SN3D CAD Model

Have a question or project enquiry you'd like to talk to us about?

Click Here To Contact Us