


# PXM6012/04S/CR Datasheet

**Product Name** // **Front Panel Mount Connector PXM6012**  
**Series 4 Contact Socket Crimp/Solder Termination**  
**(contacts available separately) Metal Body**

 [View Product Page](#)



// **Product Description:**

- |                                                                                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>Front Panel Mount Connectors</li><li>Water and dustproof to IP66, IP68, IP69K when mated with compatible connector</li><li>30 degree push twist locking, tamperproof lock prevents accidental un-mating</li><li>Socket</li><li>4 Contacts</li></ul> | <ul style="list-style-type: none"><li>Crimp/solder termination with contacts and fitting tool available separately</li><li>Metal Body</li><li>PXM6083 Sealing Cap available separately to maintain IP rating of unmated connectors</li><li>Mate with PXM6010 Series Flex Connectors</li></ul> |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

// **General Information:**

|                                 |                                |
|---------------------------------|--------------------------------|
| Product Display Title:          | Front Panel Mount Connectors   |
| Product Family:                 | Circular Power Connectors      |
| Product Series:                 | 6000 Series Buccaneer          |
| Body Colour:                    | Metallic Grey                  |
| Body Material:                  | Brass                          |
| Body Material Type:             | Metal Body                     |
| Contact Type:                   | Socket Contact                 |
| Coupling Type:                  | Push-Twist                     |
| Current Max:                    | 10A, 4A, 7A                    |
| Diameter Over Coupling Ring Mm: | 32mm                           |
| Function:                       | Front Panel Mount Connector    |
| Insulation Resistance:          | >10 <sup>6</sup> MΩ @500V DC   |
| Ip Rating:                      | IP66, IP68, IP69K              |
| Max Contact Accomodation Awg:   | 20AWG                          |
| Min Contact Accomodation Awg:   | 16AWG                          |
| Max Contact Accomodation Mm2:   | 1.3mm <sup>2</sup>             |
| Min Contact Accomodation Mm2:   | 0.52mm <sup>2</sup>            |
| Max Operating Temperature:      | +120°C                         |
| Min Operating Temperature:      | -40°C                          |
| Max Panel Thickness:            | 5.2mm                          |
| Min Panel Thickness:            | 0.8mm                          |
| Number Of Contacts:             | 4 Contacts                     |
| Panel Cut Out:                  | 22.50xR13.5-3.5mm              |
| Rohs Compliant:                 | Yes                            |
| Salt Spray Corrosion Test:      | EN60068-2-11 Test Ka Salt Mist |
| Thread Size:                    | M22x1.5-6g                     |
| Voltage Max:                    | 277V                           |

// **Product PDF Links**

-  6000 Series power connectors...
-  6000 Series metal body power...

// **Product 3D CAD Model Links**

-  PXM6012/04S/CR3D CAD Model



Have a question or project enquiry  
you'd like to talk to us about?



[Click Here To Contact Us](#)