PXM6034/A Datasheet



Product Name // Rewireable Flex Connector PXM6034 Series PUR CAT5e Cable Metal Body

View Product Page



// Product Description:

- O Rewireable Flex Cable Connectors
- O Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- O 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Supplied with shielded RJ45 plug
- O Choice of cable acceptance depending on part code:
- O Part codes suffixed /A have cable glands optimised for PUR jacket cable to maintain CAT5e performance
- O Part codes suffixed /B accept cable 4mm-10mm diameter
- O Choice of body material depending on part code:
- O Plastic body (part codes prefixed PXP)
- O Metal body (part codes prefixed PXM)
- O PXP6081/PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PXP6033TP, PXP6033TP/E, PXM6033TP Front Panel Mount CAT5e Couplers

// General Information:

Product Display Title: Product Family: **Product Series:** Body Material: Body Material Type: Contact Type: Coupling Type: Current Max: Diameter Over Coupling Ring Mm: Ethernet Category: Function: Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

Rewireable Flex Cable Connectors Circular Data Connectors 6000 Series - Ethernet Buccaneer Brass - Nickel Plated Metal Body Plug Contact Push-Twist 1.5A 32mm Cat 5e Flex Cable Connector IP66, IP68, IP69K 7mm 5mm +70°C -20°C 8 Contacts 42V

// Product PDF Links

6000 Series Ethernet connectors...

6000 Series Ethernet connectors...

// Product 3D CAD Model Links

PXM6034/A3D CAD Model