PXM6094/B Datasheet




Product Name // Rewireable Flex Connector PXM6094 Range 4mm-7mm Cable Metal Body









// Product Description:

- 0 Rewireable Flex Cable Connectors
- O Water and dustproof to IP68 & IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Supplied with shielded Cat6a RJ45 plug
- O Part codes suffixed /B accept cable 4mm-7mm diameter
- 0 Choice of plastic or metal body material
- O Plastic body (part codes prefixed PXP)
- Metal body (part codes prefixed PXM)
- O PXP6081/PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with all panel mount connectors & backward compatible with Cat6a variants

// General Information:

Product Display Title: Product Family:

Product Series:

Body Material:

Body Material Type:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Ethernet Category:

Function: In Rating:

Max Cable Entry Size:

Min Cable Entry Size: **Max Operating Temperature:**

Min Operating Temperature:

Number Of Contacts:

Voltage Max:

Rewireable Flex Connector 4mm-7mm Cable Metal Body

Circular Data Connectors

6000 Series Ethernet

Brass - Nickel Plated

Metal Body

Plug Contact

Push-Twist 1.5A

32mm

Cat 6a

Flex Cable Connector

IP66, IP68, IP69K

7mm

4mm +70°C

-20°C

8 Contacts

42V

// Product PDF Links



6000 Series HDMI Product Data

// Product 3D CAD Model Links



PXM6094/B3D CAD Model