
## PXP0020/A/3M00/A Datasheet



## Product Name // Flex USB A Male to USB A Male Cable Assembly 3m







## // Product Description:

- O IP67 Male USB A to Male USB A
- O IP67 when mated
- O Mates with rear panel mount connectors PXP0023, PXM0023
- O USB 2.0 Performance
- O Length 3m

## // General Information:

Product Display Title:Sealed USB Cable / Single EndedProduct Family:Circular Data ConnectorsProduct Series:20 Series USB

Product Series:20 Series USBody Colour:BlackBody Material:PVCBody Material Type:Plastic BodyCable Length:3m

Contact Pin Material:Copper, Gold platedContact Type:Plug ContactCoupling Type:Screw

Data Cable Type:
USB 2.0 Sealed A Plug to Standard A Plug
Diameter Over Coupling Ring Mm:
25.5mm

Diameter Over Coupling Ring Mm:25.5mmDurability:1500Fixing Nut Material:PlasticFlamability Rating:UL94V-Function:Flex to:

Function: Flex to Standard Connector Double Ended Cable Ip Rating: IP67

Max Operating Temperature:

Min Operating Temperature:

Number Of Contacts:

Panel Cut Out:

Rohs Compliant:

Yes

Sheath Colour:

Black

Sheath Colour:BlackSheath Material:PVCThread Size:13/16-28UN 2A

Voltage Max:

// Product PDF Links

20 Series USB Waterproof product...

// Product 3D CAD Model Links

5V

PXP0020/A/3M00/A3D CAD Model