


# PXP4012/03S Datasheet

**Product Name // Front Panel Mounting Connector - 3  
Contacts - Socket**

[View Product Page](#)


**// Product Description:**

- ◊ Front Panel Mounting Connector
- ◊ Water and dustproof to IP69K when mated with compatible connector
- ◊ 3 Contacts - Socket
- ◊ Sealing Cap available separately to maintain IP rating of unmated connectors
- ◊ Mates with PXP4000, PXP4002, and PXP4010

**// General Information:**

Product Display Title:	Front Panel Mount Connector
Product Family:	Circular Power Connectors
Product Series:	4000 Series Buccaneer
Approvals:	cUL, UL, VDE
Body Colour:	Black
Body Material:	Polycarbonate/Polybutylene Terephthalate (PC/PBT)
Body Material Type:	Plastic Body
Contact Type:	Socket Contact
Coupling Type:	Bayonet Lock
Current Max:	13A
Diameter Over Coupling Ring Mm:	19.7mm
Flamability Rating:	UL94V-0
Function:	Front Panel Mount Connector
Ip Rating:	IP66, IP67, IP68, IP69K
Max Operating Temperature:	+120°C
Min Operating Temperature:	-40°C
Max Panel Thickness:	6.2mm
Number Of Contacts:	3 Contacts
Rohs Compliant:	Yes
Voltage Max:	600V

**// Product PDF Links**

[4000 Series power connectors...](#)

**// Product 3D CAD Model Links**

[PXP4012/03S3D CAD Model](#)