


Product Name // Pre-Wired Flex Cable Connector | 1m | 2
Contacts | Plug

 [View Product Page](#)



// Product Description:

- Pre-Wired Flex Cable Connector
 - Water and dustproof to IP66 & IP68 when mated with compatible connector
 - 30 degree push twist locking, tamperproof lock prevents accidental un-mating
 - Plug
 - 2 contacts
- 1m cable fitted
 - Plastic body with overmould
 - PXP6081 Sealing Cap available separately to maintain IP rating of unmated connector
 - Mates with PXP6001 & PXP6011 Series Inline, PXP6012 & PXP6014 Series Front Panel Mount Connectors

// General Information:

Product Display Title:	Pre-Wired Flex Cable Connector - 1m - 2 Contacts - Plug
Product Family:	Circular Power Connectors
Approvals:	UL, VDE
Body Colour:	Black
Body Material:	Polyamide (PA)
Body Material Type:	Plastic Body
Cable Length:	1m
Contact Type:	Plug Contact
Coupling Type:	Push-Twist
Current Max:	20A
Diameter Over Coupling Ring Mm:	32mm
Flamability Rating:	UL94V-0
Function:	Flex Cable Connector
Insulation Resistance:	>10 ⁹ MΩ @500V DC
Ip Rating:	IP66, IP68
Min Contact Accomodation Awg:	14AWG
Min Contact Accomodation Mm2:	2mm2
Max Operating Temperature:	75°C
Min Operating Temperature:	-35°C
Number Of Contacts:	2 Contacts
Rohs Compliant:	Yes
Salt Spray Corrosion Test:	EN60068-2-52 Test Kb Salt Mist (Cyclic) Marine Severity Level 1
Voltage Max:	600V

// Product PDF Links



// Product 3D CAD Model Links



Have a question or project enquiry
you'd like to talk to us about?



[Click Here To Contact Us](#)