


Product Name // Pre-Wired Flex Cable Connector | 1m | 8
Contacts | Plug

 [View Product Page](#)



// Product Description:

- Pre-Wired Flex Cable Connector
- Water and dustproof to IP66 & IP68 when mated with compatible connector
- 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- Plug
- 8 contacts
- 1m cable fitted
- Plastic body with overmould
- PXP6081 Sealing Cap available separately to maintain IP rating of unmated connector
- Mates with PXP6001 & PXP6011 Series Inline, PXP6012 & PXP6014 Series Front Panel Mount Connectors

// General Information:

Product Display Title:	Pre-Wired Flex Cable Connector - 1m - 8 Contacts - Plug
Product Family:	Circular Power Connectors
Approvals:	UL, VDE
Body Colour:	Black
Body Material:	Polyamide (PA)
Body Material Type:	Plastic Body
Cable Length:	1m
Contact Type:	Plug Contact
Coupling Type:	Push-Twist
Current Max:	7A
Diameter Over Coupling Ring Mm:	32mm
Flamability Rating:	UL94V-0
Function:	Flex Cable Connector
Insulation Resistance:	>10 ⁹ MΩ @500V DC
Ip Rating:	IP66, IP68
Min Contact Accomodation Awg:	18AWG
Min Contact Accomodation Mm2:	0.82mm2
Max Operating Temperature:	75°C
Min Operating Temperature:	-35°C
Number Of Contacts:	8 Contacts
Rohs Compliant:	Yes
Salt Spray Corrosion Test:	EN60068-2-52 Test Kb Salt Mist (Cyclic) Marine Severity Level 1
Voltage Max:	600V

// Product PDF Links

 [6000 Power Buccaneer](#)

// Product 3D CAD Model Links

 [PXP6000/001/08P3D CAD Model](#)