## PXP6010/04S/CR/0709 Datasheet



Product Name // Flex Cable Connector PXP6010 Series 4 **Contact Socket Crimp/Solder Termination (contacts** available separately) 7mm-9mm Cable (Yellow Gland) **Plastic Body** 





hage not found or type unknown

## // Product Description:

- Flex Cable Connectors 0
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Socket
- 0
- 0 Crimp/solder termination with contacts and fitting tool available separately
- O Plastic Body
- 0 Cable acceptance 7mm-9mm diameter
- Gland Pack PXP6088 available separately to accomodate all
- PXP6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXP6011 Series Inline, PXP6012 and PXP6014 Series Front Panel Mount Connectors

## // General Information:

**Product Display Title: Product Family: Product Series: Body Colour:** 

**Body Material: Body Material Type:** Contact Type:

Coupling Type: **Current Max:** 

Diameter Over Coupling Ring Mm:

Flamability Rating: Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** Rohs Compliant: Salt Spray Corrosion Test:

Voltage Max:

Flex Cable Connectors Circular Power Connectors 6000 Series Buccaneer

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body Socket Contact Push-Twist 10A, 4A, 7A 32mm UL94V-0

Flex Cable Connector >106MΩ @500V DC IP66, IP68, IP69K 9mm

18AWG 20AWG 1.5mm2 0.5mm2 +120°C -40°C 4 Contacts

EN60068-2-52 Test Kb Salt Mist (Cyclic) Marine Severity Level 1

// Product PDF Links 6000 Series power connectors..

6000 Series metal body power...

// Product 3D CAD Model Links PXP6010/04S/CR/07093D CAD Model

Click Here To Contact Us