
## PXP6012/03P/CR Datasheet



## Product Name // Front Panel Mount Connector PXP6012 Series 3 Contact Plug Crimp/Solder Termination (contacts available separately) Plastic Body







## // Product Description:

- 0 Front Panel Mount Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Plug
- 0 3 Contacts

- Crimp/solder termination with contacts and fitting tool available separately
- Plastic Body
- PXP6083 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXP6010 Series Flex Connectors

## // General Information:

**Product Display Title:** 

**Product Family:** 

**Product Series:** Approvals:

**Body Colour:** 

**Body Material:** 

**Body Material Type:** 

Contact Type:

Coupling Type: **Current Max:** 

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Insulation Resistance:

Max Contact Accomodation Awg: Min Contact Accomodation Awg:

Max Contact Accomodation Mm2:

Min Contact Accomodation Mm2:

Max Operating Temperature: Min Operating Temperature:

Max Panel Thickness:

Min Panel Thickness:

**Number Of Contacts:** 

Panel Cut Out: **Rohs Compliant:** 

Salt Spray Corrosion Test:

Thread Size: Voltage Max: Front Panel Mount Connectors

Circular Power Connectors

6000 Series Buccaneer cUL, UL, VDE

Grey

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plug Contact Push-Twist

16A, 11A

32mm

UL94V-0

Front Panel Mount Connector

 $>10^6 M\Omega$  @500V DC

IP66, IP68, IP69K

14AWG

14AWG 0.52mm2

0.52mm2

+120°C

-40°C

5.2mm 0.8mm

3 Contacts

22.50xR13.5-3.5mm

EN60068-2-52 Test Kb Salt Mist (Cyclic) Marine Severity Level 1

M22x1.5-6g

277V



