
PXP6014/03P/CR Datasheet



Product Name // Screwed Front Panel Mount Connector PXM6014 Series 3 Contact Plug Crimp/Solder Termination (contacts available separately) Plastic Body

View Product Page





// Product Description:

- 0 Screwed Front Panel Mount Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Plug
- 0 3 Contacts

- Crimp/solder termination with contacts and fitting tool available separately
- Plastic Body
- PXP6083 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PXP6010 Series Flex Connectors

// General Information:

Product Display Title:

Product Family:

Product Series: Body Colour:

Body Material:

Body Material Type:

Contact Type:

Coupling Type:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Insulation Resistance:

Ip Rating:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2:

Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Min Panel Thickness:

Number Of Contacts: Panel Cut Out: **Rohs Compliant:**

Salt Spray Corrosion Test:

Thread Size: Voltage Max: Screwed Front Panel Mount Connectors

Circular Power Connectors 6000 Series Buccaneer

Grey

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body Plug Contact Push-Twist 32mm UL94V-0

Front Panel Mount Connector

>106MΩ @500V DC IP66, IP68, IP69K

14AWG 18AWG 1.5mm2 0.75mm2 +120°C -40°C 6mm 3 Contacts

EN60068-2-52 Test Kb Salt Mist (Cyclic) Marine Severity Level 1

M24x1.5 277V

// Product PDF Links

6000 Series power connectors..

6000 Series metal body power...

// Product 3D CAD Model Links

PXP6014/03P/CR3D CAD Model