# PXP6034/B Datasheet




# Product Name // Rewireable Flex Connector PXP6034 **Series 4mm-7mm Cable Plastic Body**

View Product Page







#### // Product Description:

- 0 Rewireable Flex Cable Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Supplied with shielded RJ45 plug
- 0 Choice of cable acceptance depending on part code:
- 0 Part codes suffixed /A have cable glands optimised for PUR jacket cable to maintain CAT5e performance
- O Part codes suffixed /B accept cable 4mm-7mm diameter
- O Choice of body material depending on part code:
- O Plastic body (part codes prefixed PXP)
- 0 Metal body (part codes prefixed PXM)
- 0 PXP6081/PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXP6033TP, PXP6033TP/E, PXM6033TP Front Panel Mount CAT5e Couplers

## // General Information:

**Product Display Title:** 

**Product Family:** 

**Product Series:** 

Approvals:

**Body Material:** 

**Body Material Type:** 

Contact Type:

Coupling Type:

**Current Max:** 

Diameter Over Coupling Ring Mm: **Ethernet Category:** 

Flamability Rating:

Function:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Operating Temperature: Min Operating Temperature:

**Number Of Contacts:** 

Voltage Max:

Rewireable Flex Cable Connectors

Circular Data Connectors

6000 Series - Ethernet Buccaneer

CSA, UL, VDE

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body

Plug Contact

Push-Twist

1.5A 32mm

Cat 5e

UL94V-0

Flex Cable Connector

IP66, IP68, IP69K

7mm 4mm

+120°C

-40°C

8 Contacts

42V

### // Product PDF Links



6000 Series Ethernet connectors...



6000 Series Ethernet connectors...

// Product 3D CAD Model Links

PXP6034/B3D CAD Model