
## PXP6040/A/2M00 Datasheet



## Product Name // Plastic Body Overmoulded USB Cable PXP6040 Series Standard B Plug to Sealed A Plug 2M Cable





## // Product Description:

- O Pre-Wired Plastic Body Overmoulded USB V2.0 Cable
- Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Two versions:
- Part codes containing /A are Standard USB Type B plug to Sealed Standard USB Type A plug
- Part codes containing /B are Standard USB Type A plug to Sealed Standard USB Type B plug
- O Choice of cable lengths depending on part code
- PXP6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with 6000 Series Plastic Body USB Panel Mount Connectors

## // General Information:

Product Display Title:

Product Family:

Product Series:

Approvals:

Body Material: Cable Length:

Contact Type:

Coupling Type:

Current Max:

Data Cable Type:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Max Operating Temperature: Min Operating Temperature: Number Of Contacts:

Voltage Max:

Pre-Wired Plastic Body Overmoulded USB V2.0 Cable

Circular Data Connectors

6000 Series - USB Buccaneer

CSA, UL, VDE

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

2m

Plug Contact Push-Twist

Push-Twist

1A

Standard B Plug to Sealed A Plug

32mm

UL94V-0

Flex to Standard Connector Double Ended Cable

IP66, IP68, IP69K

+120°C

-40°C

4 Contacts

30V

// Product PDF Links

**6000** 

6000 Series USB connectors product...

// Product 3D CAD Model Links

**⊗** ©AD

PXP6040/A/2M003D CAD Model