
PXP6043/A3 Datasheet



Product Name // Plastic Body Front Panel Mount Leaded **USB Connector Sealed 3.0 A Socket Front of Panel To 10 Way Crimp Connector**







// Product Description:

- 0 Plastic Body Front Panel Mount Leaded Connector
- 0 Water and dustproof to IP68 & IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- Sealed Standard USB 3.0 socket to lead cable terminated in 10 way crimp connector
- PXP6083 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Plastic Body USB A Cables

// General Information:

Product Display Title:

Product Family: Product Series:

Body Material:

Body Material Type:

Contact Type:

Coupling Type:

Current Max:

Data Cable Type:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** Voltage Max:

Plastic Body Front Panel Mount Leaded USB Connector Sealed A Socket

Front of Panel To 10 Way Crimp Connector

Circular Data Connectors

6000 Series - USB Buccaneer

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body

Socket Contact

Push-Twist

Sealed A Socket to 10 Way Crimp

32mm

UL94V-0

Front Panel Mount Connector

IP66, IP68, IP69K

+70°C

0°C

8 Contacts

30V

// Product PDF Links

6000 Series HDMI Product Data

// Product 3D CAD Model Links



PXP6043/A33D CAD Model