## PXP6060/3M00 Datasheet



View Product Page

bulgin



# 

### // Product Description:

- O Pre-Wired Plastic Body Overmoulded HDMI Cable
- O Water and dustproof to IP68 & IP69K when mated with compatible connector
- O 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Choice of cable lengths
- O PXP6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with 6000 Series HDMI Panel Mount Connectors

### // General Information:

**Product Display Title: Product Family: Product Series: Body Material: Body Material Type:** Cable Length: Contact Type: Coupling Type: Data Cable Type: Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

HDMI Plug to Sealed HDMI Plug 3M Cable **Circular Data Connectors** 6000 Series - HDMI Buccaneer Polycarbonate/Polybutylene Terephthalate (PC/PBT) Plastic Body 3m Plug Contact Push-Twist HDMI Plug to Sealed HDMI Plug 32mm UL94V-0 Flex to Standard Connector Double Ended Cable IP66, IP68, IP69K +70°C 0°C 19 Contacts 5V

#### // Product PDF Links

6000 Series HDMI Product Data

// Product 3D CAD Model Links

PXP6060/3M003D CAD Model

Have a question or project enquiry you'd like to talk to us about?