
PXPPVC08FIM05BCL150PVC Datashee

Product Name // M8 Series B Code PVC In-Line **Overmould Flex Cable Connector 5 Contact Pins Pre-Wired** With 15M PVC Jacket Cable





// Product Description:

- 0 M8 Series In-Line Overmould Flex Body Connectors
- 0 Water and dustproof to IP67 when mated with compatible connector
- Pin only

- Ω. 3, 4, 5 Contact (3, 4 Contact are A Code, 5 Contact are B Code)
- Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- Mate with M8 Series Flex Body and Panel Mount Connectors

// General Information:

Product Display Title: M8 Series In-Line Overmould Flex Body Connectors

Product Family: Circular Automation Connectors

Product Series: M8 Series CSA, UL Approvals: **Body Material: PVC** Cable Length: 15m

Contact Type: Plug Contact Coupling Type: Screw **Current Max:** 1.5A

Diameter Over Coupling Ring Mm: Inline Connector Single Ended Cable Function:

Ip Rating: IP67 +80°C Max Operating Temperature: Min Operating Temperature: -25°C **Number Of Contacts:** 5 Contacts Pin Layout Code: B Code Sheath Material: PVC Thread Size: M8 x 1

// Product PDF Links M8 Series automation connectors.. // Product 3D CAD Model Links PXPPVC08FIM05BCL150PVC3D CAD Mode

30V

12.5mm

Voltage Max: