PXPPVC12FBF12ACL100PVC Datasheet bulgin

Product Name // M12 Series A Code PVC Overmould Flex Body Cable Connector 12 Contact Socket Pre-Wired With 10M PVC Jacket Cable

View Product Page



// Product Description:

- O M12 Series Overmould Flex Body Connectors
- O Water and dustproof to IP67 when mated with compatible connector
- O Socket only
- 3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)
- Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- O Choice of Sealing Caps available separately to maintain IP rating of unmated connectors
- O Mate with M12 Series Inline Body and Panel Mount Connectors

// General Information:

Product Display Title: **Product Family:** Product Series: **Body Material:** Cable Length: Contact Type: Coupling Type: Current Max: **Diameter Over Coupling Ring Mm:** Function: Ip Rating: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Pin Lavout Code: Sheath Material: Thread Size: Voltage Max:

M12 Series Overmould Flex Body Connectors **Circular Automation Connectors** M12 Series PVC 10m Socket Contact Screw 1.5A 20mm Flex Connector Single Ended Cable IP67 +80°C -25°C 12 Contacts A Code PVC M12 x 1 30V

// Product PDF Links

M12 Series automation connectors..

// Product 3D CAD Model Links

PXPPVC12FBF12ACL100PVC3D CAD Mode