
PXPPVC12FIM04ACL010PVC Datasheet bulgin

Product Name // M12 Series A Code PVC In-Line Overmould Flex Cable Connector 4 Contact Pins Pre-Wired With 1M PVC Jacket Cable





// Product Description:

- M12 Series In-Line Overmould Flex Body Connectors
- Water and dustproof to IP67 when mated with compatible connector
- O Pin only
- Q 3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)
- Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- Choice of Sealing Caps available separately to maintain IP rating of unmated connectors
- Mate with M12 Series Flex Body and Panel Mount Connectors

// General Information:

Product Display Title: Product Family:

Product Series:

Body Material:

Cable Length: Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Function:

Ip Rating:

Max Operating Temperature:
Min Operating Temperature:
Number Of Contacts:
Pin Layout Code:

Sheath Material: Thread Size:

Voltage Max:

M12 Series In-Line Overmould Flex Body Connectors

Circular Automation Connectors

M12 Series

PVC

1m

Plug Contact

Screw 4A

20mm

Inline Connector Single Ended Cable

IP67 +80°C

-25°C

-25 0

A Code

A Code

PVC

M12 x 1 250V





// Product 3D CAD Model Links

