

**Product Name // M12 Series D Code PVC In-Line
Overmould Flex Cable Connector 4 Contact Pins Pre-Wired
With 1M PVC Jacket Cable**

[View Product Page](#)


// Product Description:

- ⊕ M12 Series In-Line Overmould Flex Body Connectors
- ⊕ Water and dustproof to IP67 when mated with compatible connector
- ⊕ Pin only
- ⊕ 3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)
- ⊕ Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- ⊕ Choice of Sealing Caps available separately to maintain IP rating of unmated connectors
- ⊕ Mate with M12 Series Flex Body and Panel Mount Connectors

// General Information:

| | |
|---------------------------------|---|
| Product Display Title: | M12 Series In-Line Overmould Flex Body Connectors |
| Product Family: | Circular Automation Connectors |
| Product Series: | M12 Series |
| Body Material: | PVC |
| Cable Length: | 1m |
| Contact Type: | Plug Contact |
| Coupling Type: | Screw |
| Current Max: | 4A |
| Diameter Over Coupling Ring Mm: | 20mm |
| Function: | Inline Connector Single Ended Cable |
| Ip Rating: | IP67 |
| Max Operating Temperature: | +80°C |
| Min Operating Temperature: | -25°C |
| Number Of Contacts: | 4 Contacts |
| Pin Layout Code: | D Code |
| Sheath Material: | PVC |
| Thread Size: | M12 x 1 |
| Voltage Max: | 250V |

// Product PDF Links

[M12 Series automation connectors...](#)

// Product 3D CAD Model Links

[PXPPVC12FIM04DCL010PVC3D CAD Mode](#)


Have a question or project enquiry
you'd like to talk to us about?



[Click Here To Contact Us](#)