
PXPTPU08FIM04ACL020PUR Datasheet

Product Name // M8 Series A Code TPU In-Line Overmould Flex Cable Connector 4 Contact Pins Pre-Wired With 2M PUR Jacket Cable

🚯 View Product Page





// Product Description:

- O M8 Series In-Line Overmould Flex Body Connectors
- O Water and dustproof to IP67 when mated with compatible
- O Pin only

connector

- O 3, 4, 5 Contact (3, 4 Contact are A Code, 5 Contact are B Code)
- Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- O Mate with M8 Series Flex Body and Panel Mount Connectors

// General Information:

Product Display Title: **Product Family: Product Series:** Approvals: **Body Material:** Cable Length: Contact Type: Coupling Type: Current Max: Diameter Over Coupling Ring Mm: Function: Ip Rating: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Pin Layout Code: Sheath Material: Thread Size: Voltage Max:

M8 Series In-Line Overmould Flex Body Connectors **Circular Automation Connectors** M8 Series CSA, ENEC, UL, VDE TPU 2m Plug Contact Screw ЗA 12.5mm Inline Connector Single Ended Cable IP67 +80°C -25°C 4 Contacts A Code PUR M8 x 1 30V

// Product PDF Links

M8 Series automation connectors...

// Product 3D CAD Model Links

PXPTPU08FIM04ACL020PUR3D CAD Mode