

## PXPTPU12FIM03ACL150PUR Datashee

## Product Name // M12 Series A Code TPU In-Line







## // Product Description:

- 0 M12 Series In-Line Overmould Flex Body Connectors
- 0 Water and dustproof to IP67 when mated with compatible connector
- 0 Pin only
- O 3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)
- Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- O Choice of Sealing Caps available separately to maintain IP rating of unmated connectors
- Mate with M12 Series Flex Body and Panel Mount Connectors

## **General Information:**

**Product Display Title:** M12 Series In-Line Overmould Flex Body Connectors

**Product Family:** Circular Automation Connectors

**Product Series:** M12 Series

TPU **Body Material:** Cable Length: 15m Contact Type: Plug Contact

Coupling Type: Screw Current Max: 4A Diameter Over Coupling Ring Mm: 20mm

Inline Connector Single Ended Cable

Ip Rating: **IP67** +80°C Max Operating Temperature: -25°C Min Operating Temperature: **Number Of Contacts:** 3 Contacts Pin Layout Code: A Code

Sheath Material: PUR Thread Size: Voltage Max:

M12 x 1 250V





// Product 3D CAD Model Links PXPTPU12FIM03ACL150PUR3D CAD Mode