## PXPTPU12FIM04DCL100PUR Datashee

## Product Name // M12 Series D Code TPU In-Line **Overmould Flex Cable Connector 4 Contact Pins Pre-Wired** With 10M PUR Jacket Cable





## // Product Description:

- 0 M12 Series In-Line Overmould Flex Body Connectors
- 0 Water and dustproof to IP67 when mated with compatible connector
- 0 Pin only
- 3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)
- Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- O Choice of Sealing Caps available separately to maintain IP rating of unmated connectors
- Mate with M12 Series Flex Body and Panel Mount Connectors

## **General Information:**

**Product Display Title:** 

**Product Family: Product Series:** 

**Body Material:** Cable Length:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Ip Rating:

Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** 

Pin Layout Code: Sheath Material:

Thread Size: Voltage Max: M12 Series In-Line Overmould Flex Body Connectors

Circular Automation Connectors

M12 Series

TPU

10m

Plug Contact

Screw 4A

20mm

Inline Connector Single Ended Cable

**IP67** +80°C

-25°C

4 Contacts

D Code PUR

M12 x 1

250V



M12 Series automation connectors.

// Product 3D CAD Model Links

