PXPTPU12FIM12ACL050PUR Datasheet bulgin

Product Name // M12 Series A Code TPU In-Line Overmould Flex Cable Connector 12 Contact Pins Pre-Wired With 5M PUR Jacket Cable





// Product Description:

- O M12 Series In-Line Overmould Flex Body Connectors
- Water and dustproof to IP67 when mated with compatible connector
- O Pin only
- Q 3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)
- Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- O Choice of Sealing Caps available separately to maintain IP rating of unmated connectors
- Mate with M12 Series Flex Body and Panel Mount Connectors

// General Information:

Product Display Title:

Product Family: Product Series:

Body Material:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Function:

Ip Rating:

Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Pin Layout Code:

Sheath Material:

Thread Size: Voltage Max: M12 Series In-Line Overmould Flex Body Connectors

Circular Automation Connectors

M12 Series

Division

Plug Contact

Screw

1.5A 20mm

Inline Connector Single Ended Cable

IP67

+80°C -25°C

12 Contacts

A Code

PUR

M12 x 1

30V

// Product PDF Links



// Product 3D CAD Model Links

