PXPTPU12FIM12ACL100PUR Datashee

Product Name // M12 Series A Code TPU In-Line **Overmould Flex Cable Connector 12 Contact Pins Pre-Wired** With 10M PUR Jacket Cable





// Product Description:

- 0 M12 Series In-Line Overmould Flex Body Connectors
- 0 Water and dustproof to IP67 when mated with compatible connector
- 0 Pin only
- O 3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)
- Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- O Choice of Sealing Caps available separately to maintain IP rating of unmated connectors
- Mate with M12 Series Flex Body and Panel Mount Connectors

General Information:

Product Display Title:

Product Family: Product Series:

Body Material:

Cable Length:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Ip Rating:

Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** Pin Layout Code:

Sheath Material: Thread Size:

Voltage Max:

M12 Series In-Line Overmould Flex Body Connectors

Circular Automation Connectors

M12 Series

TPU

10m

Plug Contact

Screw 1.5A

20mm

Inline Connector Single Ended Cable

IP67

+80°C -25°C

12 Contacts

A Code

PUR

M12 x 1

30V

// Product PDF Links

M12 Series automation connectors.

// Product 3D CAD Model Links

PXPTPU12FIM12ACL100PUR3D CAD Mode