PXPTPU78FBF05ASTM22 Datasheet

Product Name // 5 Contacts 7/8" Flex Body Female

View Product Page

🔬 <u>bulg</u>in



// Product Description:

Connector

- O 5 Contacts 7-8" Flex Body Female Connector
- O IP67 rated when mated
- O Mechanical Cycles >100

- Operating Temperature -25°C to +85°C
- O Rated Voltage 300 V
- O ROHS compliance

// General Information:

Product Display Title: Product Family: Product Series: **Connection Method:** Contact Pin Material: Min Coupling Torque: Max Coupling Torque: Contact Type: Current Max: Durability: Function: Insulation Resistance: Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Operating Temperature: Min Operating Temperature: Nominal Cross Sectional Area Mm2: Number Of Contacts: Pin Layout Code: **Rohs Compliant:** Thread Size: Voltage Max:

7/8" Flex Body Female Connector Circular Automation Connectors 7/8" Series Screw Phosphor bronze gold plated 1u" 0.4Nm 0.8Nm Socket Contact 9A >100 Cycles Flex Body Female Connector >100MOhm IP67 12mm 6mm +85°C -25°C 1.5mm2 5 Contacts A Code Yes M22 300V

// Product PDF Links

78 Series Circular connectors...

// Product 3D CAD Model Links

PXPTPU78FBF05ASTM223D CAD Model