
PXPTPU78FIM05ASTM22 Datasheet



Product Name // 5 Contacts 7/8" Flex Body Male Connector







// Product Description:

- 5 Contacts 7-8" Flex Body Male Connector
- O IP67 rated when mated
- Mechanical Cycles >100

- Operating Temperature -25°C to +85°C
- O Rated Voltage 300 V
- ROHS compliance

// General Information:

Product Display Title:

Product Family: Product Series:

Connection Method:

Contact Pin Material:

Min Coupling Torque:

Max Coupling Torque:

Contact Type: Current Max:

Durability:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Operating Temperature:

Min Operating Temperature:

Nominal Cross Sectional Area Mm2:

Number Of Contacts: Pin Layout Code: Rohs Compliant:

Thread Size: Voltage Max: 7/8" Right Angled Male Connector

Circular Automation Connectors

7/8" Series

Screw

Brass gold plated 1u"

0.4Nm

0.8Nm

Plug Contact

9A

>100 Cycles

Flex Body Male Connector

>100MOhm

IP67

6mm

+85°C

-25°C

1.5mm25 Contacts

A Code

Yes M22

300V

// Product PDF Links



79 Carias Circular connectors

// Product 3D CAD Model Links



PXPTPU78FIM05ASTM223D CAD Model