

PXV0411/02P/6570 Datasheet

Product Name // Vitalis Inline Cable Connector PXV0411 2
Contact Plug 6.5mm-7.0mm Cable

 [View Product Page](#)



// **Product Description:**

- ⬢ PXV0411/02P/6570 provides an average PCF reduction of 6.1kg CO2e per 100 units vs. the equivalent Standard 400 Series part number
 - ⬢ Inline Cable Connector
 - ⬢ Water and dustproof to IP68 when mated with compatible connector
 - ⬢ Plug
 - ⬢ 2 Contact
- ⬢ 8A Crimp or Solder Contacts available (supplied separately)
 - ⬢ Contact insertion and crimp tools available (supplied separately)
 - ⬢ 6.5mm to 7.0mm cable acceptance
 - ⬢ PXV0480/1 Sealing Cap available separately to maintain IP rating of unmated connectors
 - ⬢ Mate with Flex Cable Connectors PXV0410

// **General Information:**

Product Display Title:	Inline Cable Connector
Product Family:	Circular Power Connectors
Approvals:	cULus(Pending), VDE(Pending)
Body Material:	Polyamide (PA)
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	8A
Diameter Over Coupling Ring Mm:	19.1mm
Flamability Rating:	UL94V-0
Function:	Inline Cable Connector
Ip Rating:	IP68, IP69K
Max Cable Entry Size:	7.0mm
Min Cable Entry Size:	6.5mm
Max Contact Accomodation Awg:	20AWG
Min Contact Accomodation Awg:	24AWG
Max Contact Accomodation Mm2:	0.5mm2
Min Contact Accomodation Mm2:	0.25mm2
Max Operating Temperature:	+80°C
Min Operating Temperature:	-40°C
Number Of Contacts:	2 Contacts
Rohs Compliant:	Yes
Voltage Max:	250V

// **Product PDF Links**



// **Product 3D CAD Model Links**



Have a question or project enquiry
you'd like to talk to us about?



[Click Here To Contact Us](#)