

PXV0411/04P/4045 Datasheet



Product Name // Vitalis Inline Cable Connector PXV0411 4  
Contact Plug 4.0mm-4.5mm Cable

[View Product Page](#)



// Product Description:

- PXV0411/04P/4045 provides an average PCF reduction of 6.0kg CO2e per 100 units vs. the equivalent Standard 400 Series part number
- Inline Cable Connector
- Water and dustproof to IP68 when mated with compatible connector
- Plug
- 4 Contact
- 5A Crimp or Solder Contacts available (supplied separately)
- Contact insertion and crimp tools available (supplied separately)
- 4.0mm to 4.5mm cable acceptance
- PXV0480/1 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Flex Cable Connectors PXV0410

// General Information:

|                                 |                              |
|---------------------------------|------------------------------|
| Product Display Title:          | Inline Cable Connector       |
| Product Family:                 | Circular Power Connectors    |
| Approvals:                      | cULus(Pending), VDE(Pending) |
| Body Material:                  | Polyamide (PA)               |
| Body Material Type:             | Plastic Body                 |
| Contact Type:                   | Plug Contact                 |
| Coupling Type:                  | Screw                        |
| Current Max:                    | 5A                           |
| Diameter Over Coupling Ring Mm: | 19.1mm                       |
| Flamability Rating:             | UL94V-0                      |
| Function:                       | Inline Cable Connector       |
| Ip Rating:                      | IP68, IP69K                  |
| Max Cable Entry Size:           | 4.5mm                        |
| Min Cable Entry Size:           | 4.0mm                        |
| Max Contact Accomodation Awg:   | 22AWG                        |
| Min Contact Accomodation Awg:   | 26AWG                        |
| Max Contact Accomodation Mm2:   | 0.34mm2                      |
| Min Contact Accomodation Mm2:   | 0.14mm2                      |
| Max Operating Temperature:      | +80°C                        |
| Min Operating Temperature:      | -40°C                        |
| Number Of Contacts:             | 4 Contacts                   |
| Rohs Compliant:                 | Yes                          |
| Voltage Max:                    | 125V                         |

// Product PDF Links



// Product 3D CAD Model Links



Have a question or project enquiry  
you'd like to talk to us about?



[Click Here To Contact Us](#)