

Product Name // Vitalis Inline Cable Connector PXV0411 4
Contact Socket 6.0mm-6.5mm Cable

 View Product Page



// Product Description:

- ⬢ PXV0411/04S/6065 provides an average PCF reduction of 6.0kg CO2e per 100 units vs. the equivalent Standard 400 Series part number
 - ⬢ Inline Cable Connector
 - ⬢ Water and dustproof to IP68 when mated with compatible connector
 - ⬢ Socket
 - ⬢ 4 Contact
- ⬢ 5A Crimp or Solder Contacts available (supplied separately)
 - ⬢ Contact insertion and crimp tools available (supplied separately)
 - ⬢ 6.0mm to 6.5mm cable acceptance
 - ⬢ PXV0480/1 Sealing Cap available separately to maintain IP rating of unmated connectors
 - ⬢ Mate with Flex Cable Connectors PXV0410

// General Information:

Product Display Title:	Inline Cable Connector
Product Family:	Circular Power Connectors
Approvals:	cULus(Pending), VDE(Pending)
Body Material:	Polyamide (PA)
Body Material Type:	Plastic Body
Contact Type:	Socket Contact
Coupling Type:	Screw
Current Max:	5A
Diameter Over Coupling Ring Mm:	19.1mm
Flamability Rating:	UL94V-0
Function:	Inline Cable Connector
Ip Rating:	IP68, IP69K
Max Cable Entry Size:	6.5mm
Min Cable Entry Size:	6.0mm
Max Contact Accomodation Awg:	22AWG
Min Contact Accomodation Awg:	26AWG
Max Contact Accomodation Mm2:	0.34mm2
Min Contact Accomodation Mm2:	0.14mm2
Max Operating Temperature:	+80°C
Min Operating Temperature:	-40°C
Number Of Contacts:	4 Contacts
Rohs Compliant:	Yes
Voltage Max:	125V

// Product PDF Links



// Product 3D CAD Model Links



Have a question or project enquiry
you'd like to talk to us about?



Click Here To Contact Us