

PXV0411/10P/4550 Datasheet



Product Name // Vitalis Inline Cable Connector PXV0411 10
Contact Plug 4.5mm-5.0mm Cable

[View Product Page](#)



// Product Description:

- PXV0411/10P/4550 provides an average PCF reduction of 6.0kg CO2e per 100 units vs. the equivalent Standard 400 Series part number
- Inline Cable Connector
- Water and dustproof to IP68 when mated with compatible connector
- Plug
- 10 Contact
- 1A Crimp or Solder Contacts available (supplied separately)
- Contact insertion and crimp tools available (supplied separately)
- 4.5mm to 5.0mm cable acceptance
- PXV0480/1 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Flex Cable Connectors PXV0410

// General Information:

Product Display Title:	Inline Cable Connector
Product Family:	Circular Power Connectors
Approvals:	cULus(Pending), VDE(Pending)
Body Material:	Polyamide (PA)
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	1A
Diameter Over Coupling Ring Mm:	19.1mm
Flamability Rating:	UL94V-0
Function:	Inline Cable Connector
Ip Rating:	IP68, IP69K
Max Cable Entry Size:	5.0mm
Min Cable Entry Size:	4.5mm
Max Contact Accomodation Awg:	24AWG
Min Contact Accomodation Awg:	28AWG
Max Contact Accomodation Mm2:	0.25mm2
Min Contact Accomodation Mm2:	0.08mm2
Max Operating Temperature:	+80°C
Min Operating Temperature:	-40°C
Number Of Contacts:	10 Contacts
Rohs Compliant:	Yes
Voltage Max:	50V

// Product PDF Links



// Product 3D CAD Model Links



Have a question or project enquiry
you'd like to talk to us about?



[Click Here To Contact Us](#)