

PXV0740/P/04 Datasheet

Product Name // Vitalis Buccaneer Inline Range (6 Contact)

[View Product Page](#)


// Product Description:

- ⊕ PXV0740/P/04 provides a PCF reduction of 4.4 kg CO₂e per 100 units compared to the equivalent Standard Series Buccaneer part number
- ⊕ Inline Cable Connector
- ⊕ Water and dustproof to IP68 when mated with compatible connectors
- ⊕ Plug contacts
- ⊕ 6 pole
- ⊕ Screw contacts, supplied fitted
- ⊕ 3.5mm-5mm diameter cable acceptance
- ⊕ Cable Glands for differing cable diameters available separately individually or in packs
- ⊕ Cable Support accessory 12237/R available separately
- ⊕ PXV0733 Sealing Cap available separately to maintain IP rating of unmated connectors
- ⊕ Mates with Standard Vitalis Series (PXV) and Standard Series (PX) Buccaneer Flex Connectors

// General Information:

Product Display Title:	Vitalis Buccaneer Inline Range (6 Contact)
Product Family:	Circular Power Connector
Product Series:	Standard Vitalis Buccaneer
Approvals:	UL, VDE
Body Colour:	Black
Body Material:	Polyamide (PA)- Glass Filled
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	5A
Diameter Over Coupling Ring Mm:	38.1mm
Flamability Rating:	UL94HB
Function:	Inline Cable Connector
Insert Colour:	Black Insert And Gland Nut
Ip Rating:	IP68, IP69K
Max Cable Entry Size:	5mm
Min Cable Entry Size:	3.5mm
Max Contact Accomodation Awg:	16AWG
Min Contact Accomodation Awg:	17AWG
Max Contact Accomodation Mm2:	1.5mm ²
Min Contact Accomodation Mm2:	1mm ²
Max Operating Temperature:	+70°C
Min Operating Temperature:	-20°C
Number Of Contacts:	6 Contacts
Rohs Compliant:	Yes
Voltage Max:	277V

// Product PDF Links

[Standard Vitalis Buccaneer Product...](#)

// Product 3D CAD Model Links

[PXV0740/P/043D CAD Model](#)