

PXV0745/P/05 Datasheet

Product Name // Vitalis Buccaneer Flex Range (7 Contact)

 [View Product Page](#)



// Product Description:

- ◊ PXV0745/P/05 provides a PCF reduction of 7.7 kg CO₂e per 100 units compared to the equivalent Standard Series Buccaneer part number
- ◊ Flex Cable Connector
- ◊ Water and dustproof to IP68 when mated with compatible connectors
- ◊ Plug contacts
- ◊ 7 pole
- ◊ Screw contacts, supplied fitted
- ◊ 5mm-7mm diameter cable acceptance
- ◊ Cable Glands for differing cable diameters available separately individually or in packs
- ◊ Cable Support accessory 12237/R available separately
- ◊ PXV0734 Sealing Cap available separately to maintain IP rating of unmated connectors
- ◊ Mates with Standard Vitalis Series (PXV) and Standard Series (PX) Buccaneer Inline, Panel Mount and Flange Mount Connectors

// General Information:

Product Display Title:	Vitalis Buccaneer Flex Range (7 Contact)
Product Family:	Circular Power Connector
Product Series:	Standard Vitalis Buccaneer
Approvals:	UL, VDE
Body Colour:	Black
Body Material:	Polyamide (PA)- Glass Filled
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	5A
Diameter Over Coupling Ring Mm:	38.1mm
Flamability Rating:	UL94HB
Function:	Flex Cable Connector
Insert Colour:	Black Insert And Gland Nut
IP Rating:	IP68, IP69K
Max Cable Entry Size:	7mm
Min Cable Entry Size:	5mm
Max Contact Accommodation Awg:	16AWG
Min Contact Accommodation Awg:	17AWG
Max Contact Accommodation Mm2:	1.5mm ²
Min Contact Accommodation Mm2:	1mm ²
Max Operating Temperature:	+70°C
Min Operating Temperature:	-20°C
Number Of Contacts:	7 Contacts
Rohs Compliant:	Yes
Voltage Max:	277V

// Product PDF Links

 [Standard Vitalis Buccaneer Product...](#)

// Product 3D CAD Model Links

 [PXV0745/P/053D CAD Model](#)