


# PXV0756/P Datasheet

## Product Name // Vitalis Buccaneer Bulkhead Flange Mount Range (3 Contact)

[View Product Page](#)


### // Product Description:

- ⬡ PXV0756/P provides a PCF reduction of 5.5 kg CO<sub>2</sub>e per 100 units compared to the equivalent Standard Series Buccaneer part number
- ⬡ Bulkhead Flange Mount Connector
- ⬡ Water and dustproof to IP68 when mated with compatible connectors
- ⬡ Plug contacts
- ⬡ 3 pole with leading Earth contact
- ⬡ Screw contacts, supplied fitted
- ⬡ PXV0733 Sealing Cap available separately to maintain IP rating of unmated connectors
- ⬡ Mate with Standard Vitalis Series (PXV) and Standard Series (PX) Buccaneer Flex Cable Connectors

### // General Information:

Product Display Title:	Vitalis Buccaneer Bulkhead Flange Mount Range (3 Contact)
Product Family:	Circular Power Connector
Product Series:	Standard Vitalis Buccaneer
Approvals:	UL, VDE
Body Colour:	Black
Body Material:	Polyamide (PA)- Glass Filled
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	10A, 12A
Diameter Over Coupling Ring Mm:	38.1mm
Flamability Rating:	UL94HB
Function:	Bulkhead Flange Mount Connector
Insert Colour:	Black Insert
Ip Rating:	IP68, IP69K
Max Contact Accomodation Awg:	12AWG
Min Contact Accomodation Awg:	14AWG
Max Contact Accomodation Mm2:	4mm <sup>2</sup>
Min Contact Accomodation Mm2:	2.5mm <sup>2</sup>
Max Operating Temperature:	+70°C
Min Operating Temperature:	-20°C
Number Of Contacts:	3 Contacts
Rohs Compliant:	Yes
Voltage Max:	277V

#### // Product PDF Links

[Standard Vitalis Buccaneer Product...](#)

#### // Product 3D CAD Model Links

[PXV0756/P3D CAD Model](#)