


**Product Name // Vitalis Buccaneer Low Profile Flange
Mount Range (4 Contact)**
 [View Product Page](#)

// Product Description:

- ⊞ PXV0766/S provides a PCF reduction of 5.2 kg CO₂e per 100 units compared to the equivalent Standard Series Buccaneer part number
- ⊞ Low Profile Flange Mount Connector
- ⊞ Water and dustproof to IP68 when mated with compatible connectors
- ⊞ Socket contacts
- ⊞ 4 pole
- ⊞ Screw contacts, supplied fitted
- ⊞ PXV0733 Sealing Cap available separately to maintain IP rating of unmated connectors
- ⊞ Mates with Standard Vitalis Series (PXV) and Standard Series (PX) Buccaneer Flex Connectors

// General Information:

| | |
|---------------------------------|--|
| Product Display Title: | Vitalis Buccaneer Low Profile Flange Mount Range (4 Contact) |
| Product Family: | Circular Power Connector |
| Product Series: | Standard Vitalis Buccaneer |
| Approvals: | UL, VDE |
| Body Colour: | Black |
| Body Material: | Polyamide (PA)- Glass Filled |
| Body Material Type: | Plastic Body |
| Contact Type: | Socket Contact |
| Coupling Type: | Screw |
| Current Max: | 10A, 6A |
| Diameter Over Coupling Ring Mm: | 38.1mm |
| Flamability Rating: | UL94HB |
| Function: | Low Profile Flange Mount Connector |
| Insert Colour: | Black Insert |
| Ip Rating: | IP68, IP69K |
| Max Contact Accomodation Awg: | 16AWG |
| Min Contact Accomodation Awg: | 17AWG |
| Max Contact Accomodation Mm2: | 1.5mm ² |
| Min Contact Accomodation Mm2: | 1mm ² |
| Max Operating Temperature: | +70°C |
| Min Operating Temperature: | -20°C |
| Number Of Contacts: | 4 Contacts |
| Rohs Compliant: | Yes |
| Voltage Max: | 277V |

// Product PDF Links
 [Standard Vitalis Buccaneer Product...](#)
// Product 3D CAD Model Links
 [PXV0766/S3D CAD Model](#)