

# PXV0794/P/04 Datasheet

**Product Name // Vitalis Buccaneer Flex Range (12 Contact)**

 [View Product Page](#)



## // Product Description:

- ◊ PXV0794/P/04 provides a PCF reduction of 7.9 kg CO<sub>2</sub>e per 100 units compared to the equivalent Standard Series Buccaneer part number
- ◊ Flex Cable Connector
- ◊ Water and dustproof to IP68 when mated with compatible connectors
- ◊ Plug contacts
- ◊ 12 pole
- ◊ Crimp/Solder contacts, available separately
- ◊ 3.5mm-5mm diameter cable acceptance
- ◊ Cable Glands for differing cable diameters available separately individually or in packs
- ◊ Cable Support accessory 12237/R available separately
- ◊ PXV0734 Sealing Cap available separately to maintain IP rating of unmated connectors
- ◊ Mates with Standard Vitalis Series (PXV) and Standard Series (PX) Buccaneer Inline, Panel Mount and Flange Mount Connectors

## // General Information:

Product Display Title:	Vitalis Buccaneer Flex Range (12 Contact)
Product Family:	Circular Power Connector
Product Series:	Standard Vitalis Buccaneer
Approvals:	UL, VDE
Body Colour:	Black
Body Material:	Polyamide (PA)- Glass Filled
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	5A
Diameter Over Coupling Ring Mm:	38.1mm
Flamability Rating:	UL94HB
Function:	Flex Cable Connector
Insert Colour:	Black Insert And Gland Nut
IP Rating:	IP68, IP69K
Max Cable Entry Size:	5mm
Min Cable Entry Size:	3.5mm
Max Contact Accommodation Awg:	22AWG
Min Contact Accommodation Awg:	24AWG
Max Contact Accommodation Mm2:	0.34mm <sup>2</sup>
Min Contact Accommodation Mm2:	0.25mm <sup>2</sup>
Max Operating Temperature:	+70°C
Min Operating Temperature:	-20°C
Number Of Contacts:	12 Contacts
Rohs Compliant:	Yes
Voltage Max:	50V

## // Product PDF Links

 [Standard Vitalis Buccaneer Product...](#)

## // Product 3D CAD Model Links

 [PXV0794/P/043D CAD Model](#)