

# PXV0794/P/05 Datasheet

## Product Name // Vitalis Buccaneer Flex Range (12 Contact)

[View Product Page](#)


### // Product Description:

- ⊕ PXV0794/P/05 provides a PCF reduction of 7.9 kg CO<sub>2</sub>e per 100 units compared to the equivalent Standard Series Buccaneer part number
- ⊕ Flex Cable Connector
- ⊕ Water and dustproof to IP68 when mated with compatible connectors
- ⊕ Plug contacts
- ⊕ 12 pole
- ⊕ Crimp/Solder contacts, available separately
- ⊕ 5mm-7mm diameter cable acceptance
- ⊕ Cable Glands for differing cable diameters available separately individually or in packs
- ⊕ Cable Support accessory 12237/R available separately
- ⊕ PXV0734 Sealing Cap available separately to maintain IP rating of unmated connectors
- ⊕ Mates with Standard Vitalis Series (PXV) and Standard Series (PX) Buccaneer Inline, Panel Mount and Flange Mount Connectors

### // General Information:

Product Display Title:	Vitalis Buccaneer Flex Range (12 Contact)
Product Family:	Circular Power Connector
Product Series:	Standard Vitalis Buccaneer
Approvals:	UL, VDE
Body Colour:	Black
Body Material:	Polyamide (PA)- Glass Filled
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	5A
Diameter Over Coupling Ring Mm:	38.1mm
Flamability Rating:	UL94HB
Function:	Flex Cable Connector
Insert Colour:	Black Insert And Gland Nut
Ip Rating:	IP68, IP69K
Max Cable Entry Size:	7mm
Min Cable Entry Size:	5mm
Max Contact Accomodation Awg:	22AWG
Min Contact Accomodation Awg:	24AWG
Max Contact Accomodation Mm2:	0.34mm <sup>2</sup>
Min Contact Accomodation Mm2:	0.25mm <sup>2</sup>
Max Operating Temperature:	+70°C
Min Operating Temperature:	-20°C
Number Of Contacts:	12 Contacts
Rohs Compliant:	Yes
Voltage Max:	50V

#### // Product PDF Links

[Standard Vitalis Buccaneer Product...](#)

#### // Product 3D CAD Model Links

[PXV0794/P/053D CAD Model](#)