


**Product Name // Vitalis Buccaneer Bulkhead Flange Mount Range (12 Contact)**
[View Product Page](#)

**// Product Description:**

- ⬡ PXV0798/S provides a PCF reduction of 5.6 kg CO<sub>2</sub>e per 100 units compared to the equivalent Standard Series Buccaneer part number
- ⬡ Bulkhead Flange Mount Connector
- ⬡ Water and dustproof to IP68 when mated with compatible connectors
- ⬡ Socket contacts
- ⬡ 12 pole
- ⬡ Crimp/Solder contacts, available separately
- ⬡ PXV0733 Sealing Cap available separately to maintain IP rating of unmated connectors
- ⬡ Mate with Standard Vitalis Series (PXV) and Standard Series (PX) Buccaneer Flex Cable Connectors

**// General Information:**

Product Display Title:	Vitalis Buccaneer Bulkhead Flange Mount Range (12 Contact)
Product Family:	Circular Power Connector
Product Series:	Standard Vitalis Buccaneer
Approvals:	UL, VDE
Body Colour:	Black
Body Material:	Polyamide (PA)- Glass Filled
Body Material Type:	Plastic Body
Contact Type:	Socket Contact
Coupling Type:	Screw
Current Max:	5A
Diameter Over Coupling Ring Mm:	38.1mm
Flamability Rating:	UL94HB
Function:	Bulkhead Flange Mount Connector
Insert Colour:	Black Insert
Ip Rating:	IP68, IP69K
Max Contact Accomodation Awg:	22AWG
Min Contact Accomodation Awg:	24AWG
Max Contact Accomodation Mm2:	0.34mm2
Min Contact Accomodation Mm2:	0.25mm2
Max Operating Temperature:	+70°C
Min Operating Temperature:	-20°C
Number Of Contacts:	12 Contacts
Rohs Compliant:	Yes
Voltage Max:	50V

**// Product PDF Links**
[Standard Vitalis Buccaneer Product...](#)
**// Product 3D CAD Model Links**
[PXV0798/S3D CAD Model](#)