


Product Name // 2.4mm Jack Straight 2 Hole Flange RF Connector
 [View Product Page](#)

* Representative product image only



// Product Description:

- ⊕ 2.4mm Jack Straight 2 Hole Flange RF Connector
- ⊕ Maximum Voltage: 150V
- ⊕ Temperature range: -40°C to +85°C
- ⊕ Frequency range: 0GHz - 50GHz
- ⊕ VSWR: <1.30
- ⊕ Dielectric withstanding Voltage: >500V
- ⊕ Impedance: 50Ohm
- ⊕ Body Material: Stainless Steel Passivation
- ⊕ Contact Material: Beryllium Copper

// General Information:

Product Display Title:	2.40mm Series Pin without Extended PTFE 2 Hole Flange
Product Family:	Radio Frequency Connectors
Product Series:	2.40mm Series
Body Length:	10.80mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>20N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>500V
Durability:	>500 cycles
Flange Mount Length:	15.80mm
Function:	Female Flange Mount RF Connector
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	UNFILLED ULTEM 1000/PEI
Max Operating Temperature:	+85°C
Min Operating Temperature:	-40°C
Mount Hole Distance:	12.20mm
Min Operating Frequency:	0GHz
Max Operating Frequency:	50GHz
Pin Diameter:	1.04mm
Pin Length:	6.34mm
Voltage Max:	150V
Vswr:	<1.30

// Product PDF Links

 [2.40mm Series Product Datasheet](#)

// Product 3D CAD Model Links

 [RF240A2JEGJJ3D CAD Model](#)