
RF240A2PEGGM Datasheet



Product Name // 2.4mm Plug Straight 2 Hole Flange RF Connector







// Product Description:

- 2.4mm Plug Straight 2 Hole Flange RF Connector
- O Maximum Voltage: 150V
- 0 Temperature range: -40°C to +85°C
- Frecuency range: 0GHz 50GHz
- 0 VSWR:

- O Dielectric withstanding Voltage: >500V
- O Impedance: 500hm
- O Body Material: Stainless Steel Passivation
- O Contact Material: Beryllium Copper

General Information:

Product Display Title:

Product Family:

Product Series: Body Length:

Body Material:

Centre Contact Retention Force:

Contact Pin Material: Min Coupling Torque: Max Coupling Torque:

Dielectric Withstanding Voltage:

Durability:

Flange Mount Length:

Function: Impedance:

Insulation Resistance:

Insulator:

Max Operating Temperature: Min Operating Temperature: Mount Hole Distance: Min Operating Frequency: Max Operating Frequency:

Pin Diameter: Pin Length: Voltage Max: Vswr:

2.40mm Series Pin without Extended PTFE 2 Hole Flange

Radio Frequency Connectors

2.40mm Series

12.70mm

Stainless Steel Passivation

>20N

Beryllium Copper

0.80Nm

1.10Nm >500V

>500 cycles

15.80mm

Male Flange Mount RF Connector

50Ohm

>5000MOhm

UNFILLED ULTEM 1000/PEI

+85°C -40°C 12.20mm 0GHz 50GHz 0.86mm 8.75mm

150V

<1.30

// Product PDF Links



// Product 3D CAD Model Links



RF240A2PEGGM3D CAD Model