RF240A4JCCKG Datasheet



Product Name // 2.4mm Jack Straight 4 Hole Flange RF

Connector



// Product Description:

- O 2.4mm Jack Straight 4 Hole Flange RF Connector
- O Maximum Voltage: 150V
- O Temperature range: -40°C to +85°C
- O Frecuency range: 0GHz 50GHz
- O VSWR: <1.30

- O Dielectric withstanding Voltage: >500V
- O Impedance: 500hm
- O Body Material: Stainless Steel Passivation
- O Contact Material: Beryllium Copper

// General Information:

Product Display Title: Product Family: **Product Series:** Is Vitalis: Body Length: Body Material: **Centre Contact Retention Force:** Contact Pin Material: Min Coupling Torque: Max Coupling Torque: Dielectric Withstanding Voltage: Durability: Flange Mount Length: Function: Impedance: Insulation Resistance: Insulator: Max Operating Temperature: Min Operating Temperature: Mount Hole Distance: Min Operating Frequency: Max Operating Frequency: Pin Diameter: Pin Length: Voltage Max: Vswr:

Radio Frequency Connectors 2.40mm Series No 10.80mm Stainless Steel Passivation >20N Beryllium Copper 0.80Nm 1.10Nm >500V >500 cycles 12.70mm Female Flange Mount RF Connector 50Ohm >5000MOhm UNFILLED ULTEM 1000/PEI +85°C -40°C 8.60mm 0GHz 50GHz 1.20mm 3.00mm 150V <1.30

2.40mm Series Pin without Extended PTFE 4 Hole Flange

// Product PDF Links

2.40mm Series Product Datasheet



RF240A4JCCKG3D CAD Model