## **RF292A2JDFDK Datasheet**




# Product Name // 2.92mm Jack Straight 2 Hole Flange RF



### Connector





#### // Product Description:

- O 2.92mm Jack Straight 2 Hole Flange RF Connector
- Maximum Voltage: 250V
- C Temperature range: -40°C to +85°C
- O Frecuency range: 0GHz 40GHz
- O VSWR:

- O Dielectric withstanding Voltage: >750V
- O Impedance: 500hm
- O Body Material: Stainless Steel Passivation
- O Contact Material: Beryllium Copper

#### // General Information:

**Product Display Title:** 

Product Family:

Product Series: Body Length:

Body Material:

Centre Contact Retention Force:

Contact Pin Material:

Min Coupling Torque:

Max Coupling Torque:

Dielectric Withstanding Voltage:

Durability:

Flange Mount Length:

Function: Impedance:

Insulation Resistance:

Insulator:

Max Operating Temperature:
Min Operating Temperature:
Mount Hole Distance:

Min Operating Frequency:
Max Operating Frequency:
Pin Diameter:

Pin Length: Thread Size: Voltage Max: Vswr: 2.92mm Series Pin without Extended PTFE 2 Hole Flange

Radio Frequency Connectors

2.92mm Series

9.50mm

Stainless Steel Passivation

>20N

Beryllium Copper

0.80Nm 1.10Nm

>750V

>500 cycles

14.00mm

Female Flange Mount RF Connector

50Ohm >5000MOhm

**ULTEM 1000** 

+85°C

-40°C 10.20mm

0GHz

40GHz

0.64mm 6.84mm

1/4 36UNS 2A

250V

<1.30

#### // Product PDF Links



// Product 3D CAD Model Links



RF292A2JDFDK3D CAD Model