


Product Name // 2.92mm Jack Straight 2 Hole Flange RF Connector
[View Product Page](#)

* Representative product image only


// Product Description:

- ⊗ 2.92mm Jack Straight 2 Hole Flange RF Connector
- ⊗ Maximum Voltage: 250V
- ⊗ Temperature range: -40°C to +85°C
- ⊗ Frequency range: 0GHz - 40GHz
- ⊗ VSWR: <1.30
- ⊗ Dielectric withstanding Voltage: >750V
- ⊗ Impedance: 50Ohm
- ⊗ Body Material: Stainless Steel Passivation
- ⊗ Contact Material: Beryllium Copper

// General Information:

Product Display Title:	2.92mm Series Pin without Extended PTFE 2 Hole Flange
Product Family:	Radio Frequency Connectors
Product Series:	2.92mm Series
Body Length:	9.50mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>20N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>750V
Durability:	>500 cycles
Flange Mount Length:	14.00mm
Function:	Female Flange Mount RF Connector
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	ULTEM 1000
Max Operating Temperature:	+85°C
Min Operating Temperature:	-40°C
Mount Hole Distance:	10.20mm
Min Operating Frequency:	0GHz
Max Operating Frequency:	40GHz
Pin Diameter:	0.75mm
Pin Length:	30.00mm
Thread Size:	1/4 36UNS 2A
Voltage Max:	250V
Vswr:	<1.30

// Product PDF Links
[2.92mm Series Product Datasheet](#)
// Product 3D CAD Model Links
[RF292A2JDFES3D CAD Model](#)

 Have a question or project enquiry
 you'd like to talk to us about?

[Click Here To Contact Us](#)